



DIAMOND SAW BLADES - ASPHALT & GREEN CONCRETE

Roc-Edge™ Premium Grade Asphalt and Green Concrete Diamond Saw Blades are laser welded and designed for wet cutting asphalt, green concrete, and hard aggregate asphalt. All sizes have a 42% diamond concentration and a 10mm (.395) segment height. Deep drop segments for undercut protection is standard for cutting abrasive asphalt. Blades cut 30% faster and last up to 40% longer. Length of cuts: 20,000 to 60,000 inch feet. They are used on hand held high speed power saws and low horse power (20 hp) walk behind saws. Blades meet or exceed DOT and professional concrete/asphalt cutter specifications. HARD BOND.

DESCRIPTION	DIAMETER	THICKNESS	ARBOR	SEGMENT	ITEM	PRICE
				HEIGHT	NO.	
 CURED CONCRETE PREMIUM STEEL	12	.125	1-20mm	.395	DSB-WP-AGC-12	607.34
	14	.125	1-20mm	.395	DSB-WP-AGC-14	724.68
	12	.125	1-20mm	.395	DSB-WS-AGC-12	607.34
	14	.125	1-20mm	.395	DSB-WS-AGC-14	724.68

DIAMOND SAW BLADES - ASPHALT OVER CONCRETE

Roc-Edge™ Premium Grade Asphalt Over Concrete Diamond Saw Blades are laser welded and designed for wet cutting asphalt over cured concrete, abrasive asphalt, and very hard aggregate asphalt. Deep drop segments for undercut protection is standard for cutting abrasive asphalt. Blades cut 30% faster and last up to 40% longer. Length of cuts: 10,000 to 15,000 inch feet. They are used on hand held high speed power saws and low horse power (20 hp) walk behind saws. Blades meet or exceed DOT and professional concrete/asphalt cutter specifications. HARD BOND.

DESCRIPTION	DIAMETER	THICKNESS	ARBOR	SEGMENT	ITEM	PRICE
				HEIGHT	NO.	
 CURED CONCRETE PREMIUM STEEL	12	.142	1	.395	DSB-WP-AC-12B	521.66
	12	.155	1	.395	DSB-WP-AC-12C	607.34
	12	.250	1	.395	DSB-WP-AC-12E	794.32
	12	.375	1	.395	DSB-WP-AC-12F	1105.34
	14	.142	1	.395	DSB-WP-AC-14B	650.34
	14	.250	1	.395	DSB-WP-AC-14E	1052.00
	14	.375	1	.395	DSB-WP-AC-14F	1558.00
	16	.125	1	.433	DSB-WP-AC-16A	666.34
	18	.142	1	.433	DSB-WP-AC-18A	921.68
	20	.142	1	.433	DSB-WP-AC-20A	1087.34
	24	.155	1	.433	DSB-WP-AC-24A	1403.32
	26	.155	1	.433	DSB-WP-AC-26A	1725.00
	30	.187	1	.433	DSB-WP-AC-30A	2403.32
	36	.187	1	.433	DSB-WP-AC-36A	3396.68


DIAMOND SAW BLADES - CURED CONCRETE

ICS USA

SPECIAL PURPOSE

DIAMOND SEGMENTS

Roc-Edge™ Premium Grade Cured Concrete Diamond Saw Blades are designed for wet cutting cured and reinforced concrete, brick, concrete block, bluestone, limestone, roof tile, and all other aggregates. They are laser welded with a special matrix bond on both sides of the segments for strength and long life. Length of cuts: 6,000 to 18,000 inch feet. They are used on hand held high speed power saws and low horse power (20 hp) walk behind saws. Blades meet or exceed DOT and professional concrete/asphalt cutter specifications. SOFT BOND.

DESCRIPTION	DIAMETER	THICKNESS	ARBOR	SEGMENT	ITEM	PRICE
				HEIGHT	NO.	
 CURED CONCRETE PREMIUM STEEL	12	0.155	1	.395	DSB-WP-CC-12A	539.02
	12	0.250	1	.395	DSB-WP-CC-12E	665.66
	12	0.375	1	.395	DSB-WP-CC-12F	872.34
	14	0.155	1	.395	DSB-WP-CC-14C	593.34
	14	0.250	1	.395	DSB-WP-CC-14E	783.34
	14	0.375	1	.395	DSB-WP-CC-14F	978.00
	16	0.155	1	.395	DSB-WP-CC-16A	693.04
	18	0.142	1	.433	DSB-WP-CC-18A	826.66
	20	0.142	1	.433	DSB-WP-CC-20A	1003.34
	24	0.155	1	.433	DSB-WP-CC-24A	1366.66
	26	0.155	1	.433	DSB-WP-CC-26A	1663.34
	30	0.187	1	.433	DSB-WP-CC-30A	2210.00
	36	0.187	1	.433	DSB-WP-CC-36A	2866.68