HIGH SPEED STEEL SPIRAL FLUTED (FAST) TAPS

ICS WIS **SPECIAL PURPOSE**

GROUND THREAD

FAST SPIRAL (APPROX. 52°)



PLUG & BOTTOMING CHAMFER

Fast Spiral Fluted Taps have continuous spiral flutes to lift and discharge chips from deep blind holes in softer metals.

	PRICE				
	NC	NF	NO. OF	LIMIT	HSS
SIZE	UNC	UNF	FLUTES	NO.	SFTF
4	40	-	2	H2	14.84
5	40	-	2	H2	14.84
6	32	-	2	H3	12.00
8	32	-	3	H3	12.00
10	24	32	3	H3	12.00
12	24	-	3	H3	12.00

	PRICE				
	NC	NF	NO. OF	LIMIT	HSS
SIZE	UNC	UNF	FLUTES	NO.	SFTF
1/4	20	28	3	H3	13.02
5/16	18	24	3	H3	16.36
3/8	16	24	3	H3	18.54
7/16	14	20	3	H3	27.70
1/2	13	20	3	H3	33.42
5/8	11	18	4	H3	51.70
3/4	10	16	4	H3	66.36

HIGH SPEED STEEL SPIRAL FLUTED (REGULAR) TAPS

ICS WIS **SPECIAL PURPOSE**

GROUND THREAD

REGULAR SPIRAL (APPROX. 30°)



PLUG & BOTTOMING **CHAMFER**

Regular Spiral Fluted Taps have continuous 30° spiral flutes to lift and discharge chips from deep blind holes in steels and tough grades of aluminum.

	PRICE				
	NC	NF	NO. OF	LIMIT	HSS
SIZE	UNC	UNF	FLUTES	NO.	SFTR
4	40	-	2	H2	14.84
5	40	-	2	H2	14.84
6	32	-	2	H3	12.00
8	32	-	3	H3	12.00
10	24	32	3	H3	12.00
12	24	-	3	H3	12.00

	PRICE				
	NC	NF	NO. OF	LIMIT	HSS
SIZE	UNC	UNF	FLUTES	NO.	SFTR
1/4	20	28	3	H3	13.02
5/16	18	24	3	H3	16.36
3/8	16	24	3	H3	18.54
7/16	14	20	3	H3	27.70
1/2	13	20	3	H3	33.42
5/8	11	18	4	H3	51.70
3/4	10	16	4	H3	66.36